

UHF RFID

902~928MHz

Able to reach 3 meters



Access Control Reader

門禁型讀寫器



Model : WS-UHFREADT



Frequency:902~928MHz

Protocol:ISO18000-6B,ISO18000-6C(EPCGEN2)

Hopping:Broad-spectrum frequency hopping (FHSS)
or fixed frequency set by software.

Power:20~30dBm (Adjustable by software)

Range:Distance adjustable. Ranging 3 meters.

Voltage:DC 12V

Reading time:Single Tag 64 bytes. Reading time
< 6ms

Size:125*107.75*23.70mm

Elevator Control Reader

電梯型讀寫器



Model : WS-UHFREADS



Frequency:902~928MHz

Protocol:ISO18000-6B,ISO18000-6C(EPCGEN2)

Hopping:Broad-spectrum frequency hopping (FHSS)
or fixed frequency set by software.

Power:27dBm

Range:Distance adjustable. Ranging 3 meters.

Voltage:DC 12V

Reading time:Single Tag 64 bytes. Reading time
< 6ms

Size:102.75*48.4*20.9mm

文星電子股份有限公司

WENSHING ELECTRONICS CO.,LTD.

11054臺北市信義區崇德路82號

No.82,Chong De Rd.,Xinyi District 11054, Taipei, Taiwan
TEL: +886-2-27353055 FAX: +886-2-27328813

E-mail:sales@rf.net.tw

http://www.wenshing.com.tw

http://www.rf.net.tw